

Designation				Principal dimensions (mm)					Basic load ratings(N)		Basic load ratings(kgf)		Speed ratings(rpm)			Abutment and fillet dimensions (mm)						Weight(g)	
轴承代号				外形尺寸					额定载荷(N)		额定载荷(kgf)		极限转速(rpm)			安装尺寸(mm)						重量(g)	
Open type	With shiled	With seal VV	With seal DD	d	D	B	B1	r	Cr	Cor	Cr	Cor	Grease 脂润滑		Oil 油润滑	d <sub>a</sub>	d <sub>b</sub>	Da	Db	r <sub>a</sub>	r <sub>b</sub>	Open type	With shiled
								Min (最小)					ZZ	D-D	Z								
601X	601XZZ	-	-	1.5	6	2.5	3	0.15	330	98	34	10	75000	-	90000	2.7	3	4.8	5.04	0.15	0.15	0.33	0.38
602	602ZZ	-	-	2	7	2.8	3.5	0.15	385	127	39	13	63000	-	75000	3.2	3.8	5.8	6.2	0.15	0.15	0.51	0.58
602X	602XZZ	-	-	2.5	8	2.8	4	0.15	550	175	56	18	60000	-	71000	3.7	4.1	6.8	7	0.15	0.15	0.63	0.83
603	603ZZ	-	-	3	9	3	5	0.15	570	187	58	19	56000	-	67000	4.2	4.3	7.8	7.9	0.15	0.15	0.87	1.45
604	604ZZ	-	-	4	12	4	4	0.2	960	345	98	35	48000	-	56000	5.6	5.6	10.4	9.9	0.2	0.2	2.25	2.29
605	605ZZ	-	605DD	5	14	5	5	0.2	1330	505	135	52	40000	38000	50000	6.6	6.9	12.4	12.2	0.2	0.2	3.54	3.48
606	606ZZ	606VV	606DD	6	17	6	6	0.3	2260	835	231	85	38000	34000	45000	8	8.2	15	14.8	0.3	0.3	5.97	6.08
607	607ZZ1	607VV	607DD	7	19	6	6	0.3	2340	885	238	90	36000	32000	43000	9	9.1	17	16.5	0.3	0.3	7.67	7.51
608	608ZZ	608VV	608DD	8	22	7	7	0.3	3300	1370	335	140	34000	28000	40000	10	10.5	20	19	0.3	0.3	12.1	12.2
609	609ZZ	609VV	609DD	9	24	7	7	0.3	3350	1430	340	146	32000	24000	38000	11	12	22.8	20.5	0.3	0.3	14.5	14.7